IN THE CLAIMS

Please amend the claims as follows:

- 1. (Currently Amended) A method for post-processing a digital video signal, said digital video signal having a plurality of views with associated disparity maps, and said digital video signal having been subjected to an encoding process including a compression and a corresponding decoding process which impairs the associated disparity maps, characterized in that it—said method comprises the steps of: a first step of

 generating a projected disparity map from an eriginal impaired disparity map,; and a second step of

 filling holes within said projected disparity map, wherein the first generating step comprising—comprises the sub-step of removing isolated projected pixels on said projected disparity map by—first filtering—them.
 - 2. (Currently Amended) A—The method for post-processing a digital video signal as claimed in claim 1, characterized in that the first-filtering is performed by selection of isolated projected pixels that are surrounded by holes.
 - 3. (Currently Amended) A-The method for post-processing a digital video signal as claimed in claim 1, characterized in that the first-filtering is performed by selection of isolated projected

5

10

- pixels, which have no coherent characteristics with the ones of surrounding pixels.
 - 4. (Currently Amended) A—The method for post-processing a digital video signal as claimed in claim 2 or 3, characterized in that the first-filtering applies to both projection directions of the projected disparity map.
 - 5. (Currently Amended) A—The method for post-processing a digital video signal as claimed in claim 2 or 3, characterized in that the first-filtering comprises a sub-step of changing the disparity map projection magnitude.
 - 6. (Currently Amended) A The method for post-processing a digital video signal as claimed in any one of claims 1 to 5claim 1 or 2, characterized in that the selected isolated projected pixels are set as hole and the corresponding pixels in the original disparity map leading to these selected projected pixels are marked
 - 7. (Currently Amended) A-The method for post-processing a digital video signal as claimed in any-one-of-claims 1 to 6claim 1 or 2, characterized in that the second-filling step comprises the sub-steps of:
 - selecting a hole that is larger than a threshold (T2),

as wrong, thus leading to a modified original disparity map.

- median filtering on a selected boundary pixel value of said selected hole, taking into account the surrounding projected pixel values of said hole boundary pixel value, and
- padding the hole with the result of said median filtering.
- 8. (Currently Amended) A—The method for post-processing a digital video signal as claimed in claim 7, characterized in that when the selected boundary pixel gets a new value from the median filtering, the corresponding pixel in the original disparity map leading to said selected boundary pixel is marked as wrong and the pixel in the original disparity map corresponding to the boundary pixel with the new value is assigned said new value, thus leading to a modified original disparity map.
- 9. (Currently Amended) A—The method for post-processing a digital video signal as claimed in claim 6—or—8, characterized in that it—said method further comprises—a further third the step of:
 ______filling the wrong pixels of the modified original disparity map with one of their boundary pixel values that have the
- disparity map with one of their boundary pixel values that have the closest value to the original pixels of the original disparity map.
 - 10. (Currently Amended) A—The method for post-processing a digital video signal as claimed in claim 9, characterized in that the reconstructed view is reconstructed from the modified original disparity map.

- 11. (Currently Amended) A computer program product for a decoder, comprising a set of instructions, which, when loaded into said decoder, causes the decoder to carry out the method as claimed in elaims—claim 1-to-10.
- 12. (Currently Amended) A computer program product for a computer, comprising a set of instructions, which, when loaded into said computer, causes the computer to carry out the method as claimed in elaim 1—to 10.